

## Rear Wheel Steering

### SPECIFICATIONS

#### FASTENER TIGHTENING SPECIFICATIONS

##### Fastener Tightening Specifications

Application	Specification	
	Metric	English
Brake Hose Bracket Retaining Bolt	12 N.m	106 lb in
Control Module Bracket to Frame Bolts	10 N.m	81 lb in
Control Module to Frame Bracket Nuts	24 N.m	18 lb ft
Inner Tie Rod End to Steering Gear	100 N.m	74 lb ft
Lower Ball Joint Pinch Bolt	230 N.m	169 lb ft
Lower Ball Joint Retaining Bolts	110 N.m	81 lb ft
Outer Tie Rod End Retaining Nut to Steering Knuckle	55 N.m	40 lb ft
Park Brake Cable Bracket Retaining Bolt	65 N.m	48 lb ft
Rear Wheel Position Sensor	4 N.m	35 lb in
Steering Gear Actuator and Cover Retaining Bolts	61 N.m	45 lb ft
Steering Gear Motor To the Steering Gear, 6 mm bolts	10 N.m	89 lb in
Steering Gear Motor To the Steering Gear, 4 mm bolts	4 N.m	35 lb in
Upper Ball Joint Retaining Bolts	110 N.m	81 lb ft
Upper Ball Joint Retaining Nut	200 N.m	147 lb ft
Wheel Hub and Bearing Retaining Bolts	180 N.m	132 lb ft
Wheel Drive Shaft Retaining Nut	250 N.m	184 lb ft